


Vort Notus Slim Line Fans




De – centralised wall or ceiling mounted fans for continuous ventilation of bathrooms, toilets, kitchens or utility rooms. Splash proof IPX4. Can be ducted 4M.

TECHNICAL SPECIFICATIONS

- Sap Appendix Q Eligible
- 2 Models
 - Notus for wall ceiling and in – duct installations
 - Notus T-HCS as above with timer and R.H sensor
- Wall or ceiling mounted
- Can be ducted up to 4m
- High efficiency, electronically controlled, brushless motor
- 3 levels of performance: 5l/s or 10l/s (low speed) and 12l/s (boost)
- Very quiet operation
- Constant airflow control ensures the nominal performances in a wide range of alternative situations
- Motor shaft mounted on ball bearings
- Motor housing made of self-extinguishing (V0) polypropylene
- Flange, grille and front panel made of ABS
- IPX4 splash proof protection
- Conforms to international standards: CEI EN 60335-2-80 and Italian Standard CEI 107-53:1998



Dimensions (mm)



Vort Notus 100mm

CODE	VORT NOTUS DE-CENTRALISED CONTINUOUS MECHANICAL FAN 100MM IPX4. WALL / CEILING MOUNTING. CAN BE DUCTED 4M	BOX QTY
-------------	--	----------------

11903 100mm Vort Notus De-centralised Continuous Fan 100mm IPX44

Vort Notus Humidity Control Fan T-HCS 100mm

CODE	VORT NOTUS DE-CENTRALISED CONTINUOUS MECHANICAL FAN 100MM IPX4. T - HCS WALL / CEILING MOUNTING. CAN BE DUCTED 4M	BOX QTY
-------------	--	----------------

11177 100mm Vort Notus De-centralised Continuous Fan 100mm IPX4
c/w Humidity control and Timer

Dimensions (mm)

	A	B	C	D	ØE	F	G	H	I	KG
VORT NOTUS	194.6	182	171	164	97.8	129	40.5	22.2	8	0.8

